



INSTALLATION INSTRUCTIONS

IMPORTANT SAFETY INSTRUCTIONS

MESURES DE SECURITE A RESPECTURE

Before assembling your ACCESS LIGHTING fixture, please make sure that you carefully read through this instruction sheet. Save this instruction sheet and refer to it when additions to or changes in the fixture configuration are made.

Lisez attentivement ce manuel d'instructions. Enregistrer cette feuille d'instructions et de s'y référer lorsque les ajouts ou changements dans la configuration de montage sont faites.

CONSULT A QUALIFIED ELECTRICIAN TO ENSURE CORRECT BRANCH CIRCUIT CONDUCTOR.

CONSULTER UN ELECTRICIEN QUALIFIE POUR VOUS ASSURER QUE LES CONDUCTEURS DE LA DERIVATION SONT ADEQUATS

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

CE PRODUIT DOIT ETRE INSTALLE SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAIT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHERENTS

NOTE: The important safeguards and instructions that appear in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that can't be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

Read all instructions

Do not install this fixture in hazardous locations.

N'installez pas cet appareil dans des emplacements dangereux.

Do not install any fixture assembly closer than 6 inches from any curtain or similar combustible material.


Laisser une distance d'au moins 6 pouces entre ce luminaire et la toute surface combustible.

"WARNING Risk of Fire and Electric Shock."

"CAUTION: Risque d' Incendie et de Choc Electriques."

GENERAL INFORMATION

All electrical connections must be in accordance with all ordinances, Local and the U.S. National Electrical Codes (NEC). These fixtures are intended for mounting to a standard 4" metal octagon outlet box. The box must be directly supported by the building structure and U.L. Recognized.



COLLECTION

SQUARED

APPLICATION

CEILING

MODEL NO.

63966LEDD

63967LEDD

WHAT WE PROVIDE

- Mounting Hardware
- Metal with Acrylic shade
- LED

WHAT YOU NEED


- Screwdriver
- Wire Cutters
- Wiring Supplies as Specified by Electrical Code

Recommended Dimmers

- Lutron Skylark SELV-300P-AL
- Lutron Diva DVELV--300P-AL
- Lutron Diva DV-603
- Lutron Diva DVCL-153P
- Lutron Skylark S-300P

STEP BY STEP INSTRUCTIONS

Before starting your installation disconnect the Power by turning off the Circuit Breaker or by removing the fuse at the fuse box. Just turning the light off at the light switch is not sufficient to prevent electrical shock.



1


MOUNT THE CROSSBAR

If there is an existing fixture remove it.

Determine the desired location of the fixture.

Hold the crossbar up to the surface and mark with a pencil the location of the mounting plugs. Drill a hole and insert the supplied mounting plugs into the mounting surface.

Position the crossbar into the junction box. Align the holes of the crossbar and secure with the supplied screws.



2

MAKE WIRE CONNECTION AND MOUNT THE CANOPY TO THE CROSSBAR

Expose the supply wires from the J-box. Gently pull the supply wires through the hole in the crossbar plate.

Connect the black supply wire to the black fixture wire.

Secure with the supplied wire nuts. Connect the white

supply wire to the white fixture wire. Secure with the

supplied wire nuts. Attach the green J-Box wire around

green hexagonal head screw or connect it to the green

supply grounding wire of the fixture. Secure all wires


with electrical tape (not supplied).

Tuck all wires carefully into the J-Box.

Fit the fixture canopy up to the crossbar. Align the holes

of the canopy and crossbar. Secure with the

supplied screws.



3

RESTORE THE ELECTRICITY AND CHECK THE OPERATION OF YOUR NEW ACCESS LIGHTING FIXTURE

