



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Apex LED Pendant APP Series

Features

This modern double layer drum design provides a dramatic look and features LumaFuse™ laminated fabric/acrylic shade in 2 colors. White bottom acrylic diffuser disperses the light. Suspended with a 3 ft. adjustable rigid stem expandable up to 9 ft.

Construction

Metal housing and canopy. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Solid wood accent.

Diffuser

LumaFuse™ laminated fabric/acrylic front shade.
White bottom acrylic diffuser

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120VAC.

LED

Integrated LED modules capable of producing:
14" - 15W, 1400 source lumens
17" - 24W, 2400 source lumens
21" - 35W, 3200 source lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs, 90 CRI.

Certification

cETLus listed for damp locations.



Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date-of-purchase.

Specifications and dimensions
subject to change without notice.



3in1 color temperature
3000K/3500K/4000K



Ordering Information:

Espresso/Jute	Weathered Grey/Jute	LED	Source Lumens	Adjustable CCT	DIA.	H
APP1214LAJUDSNES-JT	APP1214LAJUDSNWG-JT	18W	1400	3000K/3500K/4000K	14-1/4"	4-1/4"
APP1524LAJUDSNES-JT	APP1524LAJUDSNWG-JT	30W	2400	3000K/3500K/4000K	17"	4-1/4"
APP1932LAJUDSNES-JT	APP1932LAJUDSNWG-JT	42W	3200	3000K/3500K/4000K	21-1/4"	4-1/4"

Espresso/Linen White	Weathered Grey/Linen White	LED	Source Lumens	Adjustable CCT	DIA.	H
APP1214LAJUDSNES-LW	APP1214LAJUDSNWG-LW	18W	1400	3000K/3500K/4000K	14-1/4"	4-1/4"
APP1524LAJUDSNES-LW	APP1524LAJUDSNWG-LW	30W	2400	3000K/3500K/4000K	17"	4-1/4"
APP1932LAJUDSNES-LW	APP1932LAJUDSNWG-LW	42W	3200	3000K/3500K/4000K	21-1/4"	4-1/4"