



| | | |
|----------------|--|--------------|
| LOCATION | | DATE |
| PREPARED BY | | QUANTITY |
| COMMENTS | | FIXTURE TYPE |
| CATALOG NUMBER | | |

Paulina LED Sconce PALS Series

Features

Cylindrical metal base with cream linen shade.
Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Polished chrome.

Diffuser

Cream linen shade.

Electrical

Input 120 VAC/ 60 Hz LED. Fixture is dimmable down to 10% of full scale with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

LED

Integrated LED modules capable of producing:
15.5W = 1200 lumens
3000K (CCT) rated for 50,000 hrs., 90 CRI.


Certification

All fixtures are cETLus listed for damp locations.
ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.



Ordering Information:

| Polished Chrome | LED | Source Lumens | CCT | H | W | D |
|-------------------|-------|---------------|-------|---------|--------|--------|
| PALS051412L30D1PC | 15.5W | 1200 | 3000K | 13-1/2" | 4-3/4" | 3-1/2" |