

INTEGRAL BRACKET

Filter Housings

W38-PRB SERIES SLIMLINE

- Available with .375" NPT or quick connect inlet/outlet
- Mounting bracket molded into cap
- Pressure relief button

W34-PRB STANDARD

- .75" NPT inlet/outlet
- Integral mounting bracket
- Pressure relief button
- Available with either clear or opaque sump
- Accepts a wide variety of 2.5" to 3" diameter cartridges



Tested and Certified by NSF International.

INTEGRAL BRACKET SPECIFICATIONS

MODEL	PART NUMBER	SUMP	CAP	I/O	OVERALL DIMENSIONS	OPERATING PRESSURE (PSI)	OPERATING TEMPERATURE	OPTIONAL ACCESSORIES MODEL NUMBER
WRO-2550	152086	GREY	BLACK	.375" NPT	5.25" X 13.5"	30-125	40-100	WW38
W34-PRB	152084	GREY	BLACK	.375" NPT	13.25" X 5.75"	30-125	40-100	WW34
WC34-PRB	152083	CLEAR	BLACK	.375" NPT	13.25" X 5.75"	30-125	40-100	WW34



REDUCES



Lead



Chemicals*



Chlorine Taste & Odor



Dissolved Solids



13845 BISHOPS DR., SUITE 200
BROOKFIELD, WI 53005 USA
P: 262.238.4400 | WWW.AMERICANPLUMBER.COM
CUSTOMER CARE: 800.279.9404
tech-support@pentair.com

© 2017 Pentair Residential Filtration, LLC.
All rights reserved.

*For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com/brands. Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.
300502 Rev C DE17