

Corsano®

Main Pull-Out Kitchen Faucet

Features

- Available in 28 finishes including 13 PVD finishes
- · All brass construction including sprayhead
- 360° rotating spout
- · One button control for aerated or spray stream
- · Spray jets have easy-to-clean surface
- · Quiet polymer-braided hose with rotating joint
- · Ceramic disc cartridge
- Max flow rate: 1.8 gpm (6.8 L/min)

Codes/Standards Applicable

Product meets or exceeds the following:

- ASME A112.18.1/CSA B125.1
- NSF 61, NSF 372, CEC & DOE
- Commonwealth of MA
- · ADA compliant



K51-110-FB-SN shown



K51-110-XX

Handle Style	Α	В	С	10-3/16" [259]
FB	8-1/8" [206]	4-1/8" [105]	3-13/16" [97]	
BFB	8-1/8" [206]	4-1/8" [105]	3-13/16" [97]	90°
ST	7-11/16" [195]	3-15/16" [100]	3-7/16" [87]	B
BST	7-11/16" [195]	3-15/16" [100]	3-7/16" [87]	8-5/16" [212]
				12-1/16" [306] 4-1/4" [108] 02-3/16" [56]
	1-5/8" ([42] 2-3/8" ([60]	max ess spacer		17-3/4" [450]
Through-Hole Specifications				3/8" compression fitting
<u>Mir</u> Ø1-1		<u>ommended</u> Ø 1-3/8"	<u>Max</u> Ø 1-3/8"	
[32m	m] [35mm]	[38mm]	

Specifications subject to change without notice

Dimensions are inches, rounded to 1/16" [Dimensions in brackets are mm, rounded to 1mm]