



40" [1016mm] Simulated Tile Barrier-Free Shower w/ 3/4" [19mm] Threshold

REAR CENTER DRAIN

## PRODUCT SPECIFICATIONS:

- Product material Acrylix<sup>TM</sup> surface with fiberglass composite reinforcement.
- Special installation instructions for this unit must be followed carefully.
- Certified to meet CSA B45.5/IAPMO Z124 Standard.
- This unit can be reinforced to meet the accessibility requirements for Type B dwellings upon request.
- Product has a Class B fire rating as determined by ASTM E-84 test method.
- Reinforced & slip resistant floor.
- Integral 1" [25mm] nailing flange.
- Integral 1" [25mm] floor nailing flange.
- Shower Floor: W-36" [914mm] x D-36" [914mm]
- All dimensions +/- 1/2" [12.8mm]
- Clarion Bathware reserves the right to change design and/or dimensions.
- Dimensions are the same for RE, MP, and all other versions of this model.

## 8940BF34

40" [1016mm] Simulated Tile Barrier-Free Shower w/ 3/4" [19mm] Threshold & Rear Center Drain

Clarion	Phone:
BATHWARE	Toll Fr
44 Amsler Ave.	Fax: (8
Shippenville PA 16254	www.c

Phone: (814) 226-5374 Toll Free: (800) 576-9228 Fax: (814) 226-0730 www.clarionbathware.com

 Signatures For Approval:
 Date:
 Dwg. #

 Customer:
 8940BF34-CUT

 Arch./Engr:
 Dwg. By: CAL

 Job Name:
 DATE: 4/28/2021

## \*\*\* IMPORTANT NOTICE \*\*\*