### 388-377 SUMMIT<sup>®</sup> PRO 1.28

# 

Round Front, SmartHeight™, Vitreous China, Two-Piece Toilet

#### **FEATURES**

- High performance MagnaFlush<sup>™</sup> flushing technology
- 1.28 gpf / 4.8 lpf high efficiency water consumption
- Round front, SmartHeight<sup>™</sup> bowl
- SmartFasten<sup>™</sup> 3-bolt tank-to-bowl connection
- PuraClean<sup>®</sup> easy-to-clean glaze
- 3' Rigid Flapper flush valve requires less force to flush, is more consistent and uses a simple universal repair part/seal
- · Fluidmaster<sup>®</sup> pilot operated anti-siphon fill valve
- 12' rough-in
- · Model 59 color match, metal trip lever
- · 2' glazed trapway
- · The Mansfield® limited lifetime warranty on china, Five-year limited warranty on tank trim
- · Available in White

### . . . . . . . . . . . . . . . . .

MODEL #	DESCRIPTION	CODES/STANDARDS	
388-377	Round front, SmartHeight™, two-piece toilet. Less toilet seat and supply.		
388	Round front, SmartHeight™ toilet bowl only. Less supply.	ADA COMPLIANT	
377	Tank and cover only, with left hand, front-mount, color match, metal trip lever. Less supply.		
TANK TRIM & R	EPLACEMENT PARTS		
59	Trip lever - color match, metal trip lever, left hand		
2036-1212	Summit® 1.28 rigid flapper flush valve		
400A	Fluidmaster® anti-siphon pilot fill valve		
2206	Anti-siphon pilot fill valve (compatible replacement)		
630-0030	Replacement flush valve seal		
386-LID	Tank lid		

MODEL 388-377

Toilet seat not included

When properly installed, this product meets the requirements for the Americans with Disabilities Act of 1990 (ADA). Refer to local plumbing codes, as they may vary by location and application.



!

SMARTHFIGHT ADA

 $\odot$ 

RUIND

## 388-377 SUMMIT® PRO 1.28

Round Front, SmartHeight™, Vitreous China, Two-Piece Toilet

#### **SPECIFICATIONS**

MODEL #	DESCRIPTION	CODES/STANDARDS
388-377	Round front, SmartHeight™ (1.28 gpf/4.8 lpf) two-piece toilet	C C C C C C C C C C C C C C C C C C C

MATERIAL	Vitreous China
WATER PRESSURE RANGE	20 to 80 PSI
FLUSH SYSTEM	MagnaFlush™ flushing technology
WATER USAGE	1.28 gpf / 4.8 lpf
WATER SURFACE AREA	8'X9'
ROUGH-IN	12'
MAP RATING	1,000 grams

TRAP DIAMETER	2'
TRAP SEAL	2-1/4'
SHIPPING WEIGHT	Model 388 - 52 lbs. (23.5 kg) Model 377 - 36 lbs. (16.3 kg)
WARRANTY	Vitreous China - Limited Lifetime Tank Trim - Limited Five Year

#### **TECHNICAL INFORMATION** TANK OPTIONS Note: these dimensions are nominal and subject to change without notice. Variation of model 377, with right hand trip 5-1/2" (140 MM) TYP. 377RH FINISHED WALL lever. 9-1/2" (241 MM) 11 1/4" (286 MM) 13-7/8" (352 MM)<sup>-</sup> $\bigcirc$ $\odot$ 18-1/4" (464 MM) 5-1/4" (133 MM) 112-3/4" (324 MM) 3/4" (19 MM) 16-3/8" (416 MM) TOILET FOOT PRINT 27-3/8 (695 MM) 19-3/8" 8-1/4" (492 MM) (210 MM) 3/8" (10 MM)-N.P.S SUPPLY 5-13/16" (148 MM) 33-9/16" (852 MM) (WATER LINE) 16-7/8" (424 MM) Ð FINISHED FLOOR 6" 12' (153 MM) (305 MM) -TYP. TYP.



Fixture performance and specifications meet or exceed ASME A112.19.2-2013/CSA B45.1-13 standards, and other state and local codes.