

P7249 LED

### Project:

Fixture Type: Location:

Contact:

Ceiling mounted • Damp location listed



### **Description:**

Close-to-ceiling, surface mount round with clean modern lines and white acrylic diffuser. DC LED light engine with 1027 delivered lumens at 3000K and 90+ CRI.

### **Specifications:**

Brushed Nickel (-09) (plated) Steel construction White acrylic diffuser Dimmable (See Dimming Notes) Ceiling pan covers a standard 4" hexagonal recessed outlet box Mounting strap for outlet box included 6" of wire supplied ENERGY STAR® qualified

### Performance:

Input Power	21.7w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens	1027
ССТ	3000 K
CRI	90
Life (hours)	54,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30°C
Warranty	5 year warranty
Labels	cULus Damp location listed
	ENERGY STAR <sup>®</sup> qualified

## P7249-0930K9

Images:



#### **Dimensions:**

Diameter: 10-3/8" Height: 3-1/2"



# P7249 LED

**Photometrics:** 

P7249-0930K9

Ceiling mounted • Damp location listed



energy A

### P7249-0930K9

P7249-0930K9				
120 V				
60 Hz				
0.181 A				
21.7				
>0.90				
<20%				
FCC 47CFR Part 15, Class B				
-30 °C to 30°C				
Yes*				
Over-voltage, over-current, short-circuit protected				
*See Dimming Notes for more information				

P7249-0930K9				
LED Light Engine: 3000 K 90 CRI				
System Wattage: 21.7				
Fixture delivered lumens: 1027				
Fixture Efficacy: 47.3				
Spacing Criteria: 1.0				
90				
90				
60'				
45				
240				
0° 15° 30°				

ZONAL LUMEN SUMMARY				
Z	ZONE	LUMENS	%LUMINAIRE	
(	)-30	178	17.3	
(	)-40	296	28.9	
(	)-60	556	54.2	
(	)-90	836	81.4	
9	90-120	130	12.6	
9	90-130	156	15.2	
ç	90-150	185	18	
9	90-180	191	18.6	
(	0-180	1027	100	



## P7249 LED

Ceiling mounted • Damp location listed



### P7249-0930K9

### **Dimming Notes:**

P7249-0930K9 is designed to be compatible with many Forward and Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### **Dimming Controls**

Lutron NTEVL-300	
Lutron DVELV-300P	
Lutron DVCL-253P	
Lutron Caseta Wireless	
Leviton 6681	
Leviton 6672	
Leviton 6674	
Lutron AYLV-600P	
Lutron NTLV-600	
Lutron MAELV-601	
Leviton AWRMG-EAW	
Lutron N-600	

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.