

One-Light LED Close-To-Ceiling

 Ceiling mounted • Damp location listed **PROGRESS LED**


Description:

Close-to-ceiling, surface mount round with clean modern lines and white acrylic diffuser. LED light engine with 1184 delivered lumens at 3000K and 90+ CRI.

Specifications:

- Urban Bronze (-174) (Painted)
- Steel Construction
- White acrylic diffuser
- 3000k color temperature.
- TM-21 54,000 hour life.
- 1,184 lumens.
- Dimmable to 10% brightness (See Dimming Notes)
- Ceiling pan covers a standard 4" octagonal recessed outlet box
- Mounting ceiling pan for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	22w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1184/53.8 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	54,000 (L70/TM-21)
FCC	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cULus Damp location listed ENERGY STAR® qualified Meets California Title 24 JA8-2016

P7253-17430K9

Images:



Dimensions:

Diameter: Diameter: 14"
Height: 3-3/4"

Glass
Width: 13"
Height: 3-1/2781"

P7253-17430K9

Dimming Notes:

P7253 is designed to be compatible with many Forward and Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTEVL-300

Lutron DVELV-300P

Lutron DVCL-253P

Lutron Caseta Wireless

Leviton 6681

Leviton 6672

Leviton 6674

Lutron AYLV-600P

Lutron NTLV-600

Lutron MAELV-601

Leviton AWRMG-EAW

Lutron N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.