

UltraHot™ Plus & Premium Technical Specifications

Technical Data



Certified to ANSI/UL Std. 499
Conforms to CAN/CSA Std. 22.2 No. 64



Tested and certified by WQA
to NSF/ANSI/CAN 372 for
lead free compliance.



Model	UltraHot Plus	UltraHot Premium
Item number	203876	203877
Phase - 50/60 Hz	1	Single
Voltage	120 V	120 V
Wattage	750 W	1440 W
Amperage	6.25 A	12 A
Electrical connection	6' (1.8 m) power cord with plug, hard-wiring optional	6' (1.8 m) power cord with plug, hard-wiring optional
Recommended circuit breaker size¹	10 A	15 A
Rated capacity	0.7 gal (2.6 l)	
Max. flow rate, hot water	0.66 gpm (2.5 l/min)	
Max. permissible pressure, outlet side	0 psi (0 bar)	
Temperature range	149–203 °F (65–95 °C)	
User interface	Illuminated LCD display	
Dimensions	H 17 ³ / ₄ " (450 mm) x W 7 ¹ / ₈ " (200 mm) x D 5 ³ / ₄ " (146 mm)	
Weight	8.0 lb (3.6 kg)	
Frost protection setting	45 °F (7 °C)	

¹ Supplied with power cord and plug. Hard-wiring optional. This is our recommendation as the manufacturer. Check local codes for compliance if necessary.